



PF-2001B

Duct Liner Spray Adhesive

PF-2001B is a solvent-based, non-flammable spray-grade adhesive designed to bond low-density fiberglass insulation to the interior and exterior of sheet metal air conditioning ducts. It is also an excellent adhesive used to bond urethane foam, felt and cork to metal, wood and plastic surfaces.

FEATURES

- ◆ Quick tack
- ◆ Good resistance to oxidation, moisture, heat and UV exposure
- ◆ Strong bond
- ◆ Excellent Sprayability

APPLICATION SUGGESTIONS

Surfaces to be sealed must be clean, dry, free from dirt, grease films and other foreign material. Stir well before using. Apply by brush, spray, or roll to metal surface uniformly. Press insulation securely into place making sure complete contact is made with adhesive. Bonds may be made immediately; open time is up to 10 minutes. Do not thin.

ASTM E84 Surface Burning Characteristics

Flame Spread.....5
Smoke Developed.....5

ASTM C-916

Meets Type IV criteria for insulation adhesives

PHYSICAL PROPERTIES:

BASE:	Synthetic Polymer	WEIGHT/GALLON:	10.0 lbs/gallon
SOLVENT:	Methylene Chloride	VOC CONTENT:	0.0 g/l (EPA Method 24)
SHELF LIFE:	12 months, unopened	VISCOSITY:	180-250 cps
SOLIDS:	27.0 +/- 1.0 %	OPEN TIME:	10 minutes
FLASHPOINT:	N/A	DRY TIME:	2 – 5 minutes
COLORS:	Green	COVERAGE:	450 – 600 sq ft / gallon
FORMALDEHYDE:	No urea formaldehyde added during adhesive manufacturing		

STORAGE & HANDLING:

Keep container lids tightly closed when not being used. Do no transfer to an unmarked container. Store between 60° and 90° F.



56 Air Station Industrial Park
Rockland, MA 02370

Phone 1-800-503-6991 Fax 1-800-231-8222

Info@itwtacc.com www.itwtacc.com

PF-2001B

Duct Liner Spray Adhesive

PRECAUTIONS:

Avoid prolonged breathing of vapors or repeated skin contact. Keep closed when not in use.

WARNING: This product contains a chemical, Methylene Chloride, known to the state of California to cause cancer.

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

Use with adequate ventilation.

Do not breathe dust, vapors or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing.

First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes. For skin contact, wash thoroughly with soap and water. If swallowed, or continued difficulty breathing, immediately call a physician, hospital emergency room or poison control center.

**KEEP OUT OF REACH OF CHILDREN
FOR PROFESSIONAL OR INDUSTRIAL USE ONLY
SALE TO CONSUMER IS IN VIOLATION OF FEDERAL LAW**

NOTICE TO PURCHASER: NO WARRANTIES, EXPRESS OR IMPLIED, ARE MADE INCLUDING MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. EXCEPT FOR PERSONAL INJURY RESULTING FROM USE OF THE PRODUCT AS DIRECTED, ITW TACC SHALL NOT BE LIABLE IN TORT OR CONTRACT FOR ANY LOSS OR DAMAGE. UNDER NO CIRCUMSTANCES SHALL ITW TACC, A DIVISION OF ILLINOIS TOOL WORKS INC., OR ITS AFFILIATES ("ITW TACC") BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES. THE USER MAY SEND A SAMPLE OF PRODUCT TO ITW TACC FOR TESTING. IF SUCH TESTING PROVES A PRODUCT DEFECTIVE, THE USER'S SOLE AND EXCLUSIVE REMEDY IS EITHER REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT OR REPLACEMENT OF THE CONTAINER OF PRODUCT. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF ITW TACC HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATIONS OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product. The information and suggestions for use contained herein are believed to be accurate, but are not to be construed as warranties. User shall determine the suitability of the product for his or her intended use and shall assume all risk associated therewith.

Please direct all inquiries regarding performance of this product to:

ITW TACC

56 Air Station Industrial Park

Rockland, MA 02370

Phone 1-800-503-6991 Fax 1-800-231-8222

info@itwtacc.com

www.itwtacc.com

Rev 6/10